

LITHIONICS BATTERY®

LITHIUM-ION IRON PHOSPHATE BATTERY SYSTEMS



MODEL NUMBER:
GTX12V302A-E1508-CS200-HK

Full UL Listed Version for OEM's: Bluetooth® APP, UL Listed Internal Heater, Fireproof Enclosure, RV-C CANbus Telemetry, Remote Switch, NeverDie® Reserve Energy, Battery Life Recorder.




INTERNAL BMS VERSION

The "BOSS 302"



Wireless Battery Monitoring via
Lithionics Battery® Monitor App



Application Note: Compatible with a Maximum Inverter Size of 3000 Watts. Do Not Connect to Larger Inverters or to Parallel-Connected Inverters. 3000W inverters must follow Published/Approved Installation Guides on the Resources/Support page of our website.

Item	Description
Model	GTX12V302A-E1508-CS200-HK
Nominal Voltage	12.8V
Nominal Capacity (Ah)	305Ah
Nominal Watt Hours	3904Wh
Internal Resistance	≤5mΩ
Charge	
Charging temperature range	-4 to 140°F (-20 to 60°C)
Charge voltage	14.4V RECOMMENDED, 14.6V MAX
Recommended float charge voltage (for)	13.4-13.6V
Recommended max charge current*	150A
Allowed max charge current*	200A
Discharge	
Discharging temperature range	-4 to 140°F (-20 to 60°C)
Operating Voltage Range	10.4V-13.4V
Recommended max discharge current*	150A
Max discharge current*	230A
Pulse discharge current (1 second)	1200A
Discharge cut-off voltage	NeverDie® Power Reserve @ 12.0V Low-Voltage Cut-Off @ 10.4V
Mechanical Characteristics	
Dimensions	
	Length 14.5"
	Width 8.5"
	Height 10.5"
Mounting Orientation	
	Upright position only (terminals up)
Weight	
	Approx. 63 LBS
Storage	
Storage	< 1 Month
Temperature & Humidity Range	-4~95°F (-20~35°C), 45~75%RH
	< 3 Months
	14~86°F (-10~30°C), 45~75%RH
	Recommended storage
	59~95°F (15~35°C), 45%RH~75%RH
Long Term Storage	If the battery needs to be stored for > 3 months the voltage
Self-discharge rate	Residual capacity ≤3% per month; ≤15% per year
	Reversible capacity ≤1.5% per month; ≤8% per year

* Maximum charging and discharging rates apply depending upon the ambient temperature and duty cycle of the system.

UL1973 tests of maximum charge and discharge current were performed at 25°C/77°F



30% Smaller than 3 x
100Ah Group31
Batteries, with Extra
5Ah to Spare

ENERGY

305 AMP HOURS

PULSE AMPS: 1200 (1 SEC)

3904 WATT-HOURS

INTERNAL NEVERDIE® BMS FEATURES

- NeverDie® Power Reserve (Spare Fuel) for Hotel Loads and Engine Cranking
- Over-Charge, Over-Discharge and Short-Circuit Protection (LVC, HVC, SCC)
- Low/High Temperature Charge/Discharge Protection
- Internal Heating Kit: Permits Charging as low as -20C/-4F
- Pushbutton On/Off switch for Safety and Storage
- Battery Gauge and Status Codes for Health Monitoring
- Bluetooth wireless telemetry with Lithionics Battery iOS and Android app
- CANbus telemetry in the RVIA RV-C format (M12)
- An alternator Field Control Circuit (FCC) (AMPSEAL8)
- Remote LED illuminated On/Off Power switch (AMPSEAL8)
- Auxiliary DC Breaker control (AMPSEAL8)

